



sokymat

VOLCANO TAG 370 Unique

Chip type:	UNIQUE – read only 64bits		* Test conditions and remarks
Physical:	Diameter:	67.8 mm ± 0.8 mm	
	Thickness:	11.5 mm ± 0.5 mm	
	Hole:	5.2 mm ± 0.4 mm	
	Material:	LCP, ultrasonic welded	
	Color:	Dark grey	
Electrical:	Operating frequency:	125 kHz ± 6 kHz	* At room temperature
Chemical:	Water immersion IP67		* 20°C, 35min, 1m
	Resist to common used solvents in automotive industry motor and gear oil, fuel, most acids and basics		
Thermal:	Storage:	-40°C to +160 °C	* 1x 1000h
		+250 °C	* 30x 10min
		+300 °C	* 1x 5min
	Shock/fatigue:	+20°C to +200 °C	* 500x 35min
	Operating:	-40°C to +85°C	
Part number:	601109		

© ASSA ABLOY ITG reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. ASSA ABLOY ITG declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

CLF 3.3.3.25 – V4 - DefKey: 32861 - 13.07.2007 - Page: 1 of 1
ASSA ABLOY Identification Technologies GmbH